
MX75 Datasheet

Overview

The Meraki **MX75** is an enterprise security appliance designed for distributed deployments that require remote administration across Medium branch environments. It is ideal for network administrators who demand both ease of deployment and a state-of-the-art feature set. The Meraki Dashboard allows for simple and easy deployment of the MX75 with minimal pre-configuration in almost any location.

Providing 3 dedicated WAN uplinks, 1 x GbE SFP port and 2 x RJ45 GbE ports. The LAN ports include 10 x RJ45 GbE ports. The MX75 is ready for deployment in a variety of enterprise environments. The MX75 appliance provides the following features:



Features

- Managed via Cisco Meraki Dashboard
- Automatic Firmware upgrades
- WAN Link Balancing
- Automatic WAN Failover
- SD-WAN over Meraki AutoVPN
- L3/L7 Stateful Firewall
- Geo based firewall rules
- 1:1 and 1:Many NAT
- Configurable VLANs / DHCP support
- Static Routing
- Client VPN endpoint
- Meraki AutoVPN and L2TP/IPSec VPN endpoint
- Active Directory integration
- Content Filtering
- Malware Protection (AMP) w/ optional Threat Grid integration
- IDS/IPS protection
- Custom Traffic Shaping
- Historical Client Usage statistics
- Netflow support
- Syslog integration
- Remote Packet Capture tools

Interfaces

- 1 x 1 Gigabit Ethernet SFP port dedicated for the WAN uplinks
- 2 x RJ45 / 1 Gigabit Ethernet port dedicated for the WAN uplinks
- 8 x RJ45 / 1 Gigabit Ethernet LAN ports
- 2 x RJ45 / 1 Gigabit Ethernet LAN ports with PoE+ capabilities
- 1 x USB 3.0 port for cellular modem back up

Context and Comparisons

	<u>MX75</u>	<u>MX85</u>
# of WAN Uplinks	3	4
Backup Cellular Uplink	Via 3rd Party USB Modem	Via 3rd Party USB Modem
Stateful Firewall Throughput	1 Gbps	1 Gbps
Maximum VPN Throughput	500 Mbps	500 Mbps
Advanced Security Throughput	750 Mbps	750 Mbps
PoE Capabilities	Yes, 2x RJ45 / 1 Gigabit Ethernet port (LAN)	Yes, 1x RJ45 / 1 Gigabit Ethernet port (WAN)

Technical Breakdown

WAN Interface

<u>MX75</u>	<u>MX85</u>
1 x Dedicated 1 Gigabit Ethernet SFP 2 x Dedicated 1 Gigabit Ethernet RJ45	2x Dedicated 1 Gigabit Ethernet SFP 2x Dedicated 1 Gigabit Ethernet RJ45
Cellular Uplink via 3rd Party USB Modem	Cellular Uplink via 3rd Party USB Modem

LAN Interface

<u>MX75</u>	<u>MX85</u>
10 x Dedicated 1 Gigabit Ethernet RJ45	8 x Dedicated 1 Gigabit Ethernet RJ45 2 x Dedicated 1 Gigabit Ethernet SFP

Throughput and Capabilities

	<u>MX75</u>	<u>MX85</u>
Recommended Use Case	Small branch with up to 200 users	Small to medium branch with up to 250 users
Max site-to-site VPN Throughput	500 Mbps	500 Mbps
Max Concurrent site-to-site VPN Tunnels	75	200
Max Stateful Firewall Throughput	1 Gbps	1 Gbps
Max Throughput with All Advanced Security features	750 Mbps	750 Mbps

Physical

	<u>MX75</u>	<u>MX85</u>
Mount Type	Desktop	Rack Mount
Dimensions (h x d x w)	1.06" x 5.83" x 11.14" 27 x 148 x 283 mm	1.7" x 9.8" x 19" 43.8 x 250 x 484.6mm
Weight	1.87 lb (0.85kg)	8.2lb (3.7kg)
Input Operating Voltage	90-264VAC (47-63Hz)	90-264VAC (47-63Hz)

PSU Model Number	MA-PWR-100WAC	N/A
Power Load (idle/max)	12W / 96W	12W / 55W
Operating Temperature	32°F to 113°F (0°C to 45°C)	32°F to 104°F (0°C to 40°C)
Humidity	5% to 95%	5% to 95%

Accessories

Accessory	Description
MA-PWR-CORD-US	1x AC Power Cable, US plug
MA-PWR-CORD-EU	1x AC Power Cable, EU plug
MA-PWR-CORD-UK	1x AC Power Cable, UK plug
MA-PWR-CORD-AU	1x AC Power Cable, AU plug



Note: Please refer to meraki.com for additional single-mode and multi-mode fiber transceiver modules

Troubleshooting

Common Event Log Messages

There are currently no MX75 specific Event Log entries, for more general information about navigating the **event log** and the types of events that could be expected, please check out our [Event Log documentation](#).